

TRACKER TECHNICAL SPECIFICATIONS

	TRACKER MODELS				
	2740	2741	2745	2746	2750
Operating Environment					
Secure standard OS	✓	✓	✓	✓	✓
Programmable software platform	✓	✓	✓	✓	✓
Software development kit	✓	✓	✓	✓	✓
Data Storage					
Data Storage	200MB+ non volatile flash standard — options to 2 GB				
Ports					
Serial ports — RS-232 with RJ45 interface	1	1	2	2	0 — 16
Console port — RS-232 with RJ45 interface	1	1	1	1	1
V.92 56K modems	1	1	1	1	0 — 16
10/100 Ethernet	1	2	1	2	0 — 16
Contact closures	No	No	4	4	0 — 64
Access Methods					
<i>Out-of-band</i>					
V.92 modem	✓	✓	✓	✓	✓
PPP	✓	✓	✓	✓	✓
<i>Side-band</i>					
VPN tunnel	✓	✓	✓	✓	✓
<i>In-band</i>					
telnet, ftp	✓	✓	✓	✓	✓
Security					
Two-factor authentication	✓	✓	✓	✓	✓
Firewall	✓	✓	✓	✓	✓
Restricted answering	✓	✓	✓	✓	✓
Audit trail	✓	✓	✓	✓	✓
Network Management					
Alerting service	✓	✓	✓	✓	✓
Logging service	✓	✓	✓	✓	✓
Monitoring service	✓	✓	✓	✓	✓
Comfort alarm	✓	✓	✓	✓	✓
SNMP capture / redirect	✓	✓	✓	✓	✓
SNMP agent	✓	✓	✓	✓	✓
Other					
Free lifetime technical support	✓	✓	✓	✓	✓
12 month warranty	✓	✓	✓	✓	✓
UL & CE compliance	✓	✓	✓	✓	✓
Secure menu interface	✓	✓	✓	✓	✓
Remote configuration	✓	✓	✓	✓	✓
Remote upgrade	✓	✓	✓	✓	✓
1U 19" rack option	✓	✓	✓	✓	✓
<i>UPS Options</i>					
1 hour	✓	✓	✓	✓	✓
4 hours	No	No	No	No	✓
Physical					
Dimensions in millimetres	190 wide x 140 deep x 32 high			260w x 216d x 44h	
Weight without UPS option	350 grams			2.14 kg	
Power via external adapter (supplied)	+5v DC			+9v DC	
MTBF	200,000 hours excluding batteries				